


In the chemical process industry, Processall equipment performs several unit operations in one process vessel, saving capital cost, floor space, and operating time, while improving product quality

In the Processall design, medium-intensity mixing elements lift and blend the product in a "mechanically fluidized bed" action. The independently operated chopping mills add high intensity shear to the product. The combined mixing and milling action of the Processall Mixmill is exceptionally well-suited to processing a variety of hard to handle liquids, powders, pastes, and slurries. It allows processors to take advantage of the excellent heat and mass transfer characteris-

tics of a fluidized bed. The Mixmill design can be adapted for high pressure reaction, filtration, and vacuum drying. Processall provides a complete customer service lab and maintains a rental fleet for clients' process and product development requirements. Production units have capacities ranging from 100 to 30,000 lbs. Lab and pilot-scale models with 2 to 150 lbs. capacity are available



Contact us today

4600 N. Mason-Montgomery Road | Mason, OH 45040 888-425-1603 | Sales@Processall.com







Chemical Applications

Typical Applications:

- Stearates
- Fertilizers
- Fire Extinguisher Powders
- Cellulose Derivatives
- Polymer Modifications
- Rigid and Flexible Plastic Compounding
- Industrial Sludge and Waste

Application Highlights:

- Most fertilizers can be processed in a Processall Mixmill. To improve material handling and to reduce product loss caused by dusting, the product is agglomerated and dried in a Mixmill drier.
- Fire-extinguisher powders are coated with liquid anti-friction lubricants
 to improve flow and material handling. The fluidized bed exposes an
 extremely large particulate surface area. Liquid lubricants can be atomized
 and sprayed into the fluid bed to be rapidly and uniformly distributed
 through the powder.

- Both liquid and solid metal stearates used in soaps or as additives in plastic pipe, electrical insulation, and vinyl siding can be made in Processall vessels. The (frequently liquid) reagents are mixed, chemically reacted, and dried to a free flowing powder in a single Processall reactor dryer. During the drying step, the fluidized bed action provides excellent contact of the particles with the heat transfer surface, while the integral, high-intensity chopping mills disperse and de-lump agglomerates formed as the product passes through the "pasty" stage. The final product can be sifted and packaged directly, usually without post-milling.
- Cellulose derivatives can be prepared at high pressures and dried under vacuum in efficient Processall Prestovac reactor driers.
- High-pressure, vapor-phase polymer modifications followed by vacuum drying and devolatization are ideally suited to Processall reactor/dryer systems.
- Rigid and flexible plastic compounding and master batching can be supplied as a complete turnkey system. This is to take advantage of the high power and rapid cooling capabilities of the Processall Mixmill.
- Industrial sludge and waste blending, dry power densification, and agglomoration are successfully performed in Processall equipment



Standard Plows



Heat Transfer Plow



Contact us today

4600 N. Mason-Montgomery Road | Mason, OH 45040 888-425-1603 | Sales@Processall.com



